

4, 5 & 7-TERMINAL INDOOR MODULAR METERING UNITS

Service Application						Reference
1Ø	3-Wire	120/240 or 208Y/120 Volts		0-200 Amperes per position		M-26
3Ø	3-Wire	240 Volts or 480 Volts (Ungrounded)		0-200 Amperes per position		M-26
3Ø	4-Wire	208Y/120 or 480Y/277 Volts		0-200 Amperes per position		M-26

Supplier	Catalog Numbers					
	1Ø			3Ø		
	3 Wire		3 Wire		4 Wire	
	120/240 Volts	208Y/120 Volts	240 Volts	480 Volts	208Y/120 Volts	480Y/277 Volts
AMP	RMR Series FMU Series	RMR Series FMU Series	RMR Series FMU Series	RMR Series FMU Series	RMR Series FMU Series	RMR Series FMU Series
Erickson	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series
Switchboard Builders Supply	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series	WMCBT Series WMS Series WMCB Series WMP Series WMPT Series EMCB Series EMCBT Series

CURRENT TRANSFORMER METERING (TRANSOCKETS) WITH OVERHEAD SERVICE ENTRANCE

Service Application					Reference	
1Ø	3-Wire	120/240 Volts		201-800 Amperes		M-20
3Ø	3-Wire	240(grounded) or 480 Volts		201-2000 Amperes		M-20
3Ø	4-Wire	208Y/120 or 480Y/277 Volts		201-2000 Amperes		M-20

Supplier	Ampere Rating	Transocket Catalog Numbers		
		120/240 Volts, 1Ø	240 Volts, 3Ø 480 Volts, 3Ø	208Y/120 Volts, 3Ø 480Y/277 Volts, 3Ø
AMP	400 400 / 600 800 1200 1600 2000	WETCTS4-3L-6 WETCT46-3L-6 WETCT8-4L-6	WETCTS4-4L-8 WETCT46-4L-8 WETCT8-4L-8 WETCT12-4L-8 WETCT16-4L-8 WETCT20-4L-8 (1)	WETCTS4-4L-12 WETCT46-4L-12 WETCT8-4L-12 WETCT12-4L-12 WETCT16-4L-12 WETCT20-4L-12 (1)
Erickson	400 800 1200 1600 2000	WE-1182-3 WE283-3	WE-1182-4 WE283-4 WECT123 WECT163 WECT203 (1)	WE-1182-5 WE283-5 WECT124 WECT164 WECT204 (1)
Milbank	400 600 / 800 1200 1600 2000	UCT4136OU-WE UCT8136OH-WE	UCT4338OU-WE UCT8338OH-WE UCT12338OH-WE UCT16338OH-WE UCT20338OH-WE (1)	UCT43413OU-WE UCT83413OH-WE UCT123413OH-WE UCT163413OH-WE UCT203413OH-WE (1)
RJB (Galva-Closure Products)	400 600 800 1200 1600 2000	WE403-6 WE603-6 WE803-6	WE403-8 WE603-8 WE803-8 WE1203-8 WE1603-8 WE2003-8 (1)	WE404-13 WE604-13 WE804-13 WE1204-13 WE1604-13 WE2004-13 (1)

(1) Obtain approval from the local Company office.

**CURRENT TRANSFORMER METERING (TRANSOCKETS)
WITH UNDERGROUND SERVICE LATERAL**

Service Application				Reference
1Ø	3-Wire	120/240 Volts	201-800 Amperes	M-21
3Ø	3-Wire	240(grounded) or 480 Volts	201-4000 Amperes	M-21
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	201-4000 Amperes	M-21

Supplier	Ampere Rating	Transocket Catalog Numbers		
		120/240 Volts, 1Ø	240 Volts, 3Ø 480 Volts, 3Ø	208Y/120 Volts, 3Ø 480Y/277 Volts, 3Ø
AMP	400 600 800 1200 1600 2000 2500 3000	WECT4-3L6 (1) WECT6-3L6 (1) WECT8-3L6 (1)	WECT4-4L8 (1) WECT6-4L8 (1) WECT8-4L8 (1) WECT12-4L8 (1) WECT16-4L8 (1) WECT20-4L8 WECT25-4L8 WECT30-4L8	WECT4-4L13 (1) WECT6-4L13 (1) WECT8-4L13 (1) WECT12-4L13 (1) WECT16-4L13 (1) WECT20-4L13 WECT25-4L13 WECT30-4L13
Erickson	400 600 800 1200 1600 2000	WE-1182-3 (1) WE283-3-USG (1) CUCT81 (1)	WE-1182-4 (1) WE283-4-USG (1) CUCT83 (1) CUCT123 CUCT163 WECT203-SG	WE-1182-5 (1) WE283-5-USG (1) CUCT84 (1) CUCT124 CUCT164 WECT204-SG
Milbank	400 600 800 1200 1600 2000 3000	UCT4136OU-WE (1) UCT6136UG-WE (1) UCT8136UG-WE (1)	UCT4338OU-WE (1) UCT6338UG-WE (1) UCT8338UG-WE (1) UCT12338UG-WE (1) UCT16338UG-WE (1) UCT20338UG-WE	UCT43413OU-WE (1) UCT63413UG-WE (1) UCT83413UG-WE (1) UCT123413UG-WE (1) UCT163413UG-WE (1) UCT203413UG-WE UCT303413UG-WE
RJB (Galva-Closure Products)	400 600 800 1200 1600 2000 3000	WE403-6 (1) WE603-6UG (1) WE803-6UG (1)	WE403-8 (1) WE603-8UG (1) WE803-8UG (1) WE1203-8UG (1) WE1603-8UG (1) WE2003-8UG	WE404-13 (1) WE604-13UG (1) WE804-13UG (1) WE1204-13UG (1) WE1604-13UG (1) WE2004-13UG WE3004-13UG

(1) See table listing manufacturers' wireways for use with direct buried service laterals.

**CURRENT TRANSFORMER METERING (TRANSOCKETS) WITH DISCONNECT
FOR OVERHEAD OR UNDERGROUND SERVICE**

Service Application				Reference
1Ø	3-Wire	120/240 Volts	201 - 800 Amperes	M-22
3Ø	3-Wire	240 (grounded B) or 480 Volts	201 - 1200 Amperes	M-22
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	201 - 1200 Amperes	M-22

Supplier	Ampere Rating	Current Transformer Cabinet with Disconnect Catalog Numbers (1)		
		120/240 Volts, 1Ø	240 Volts, 3Ø 480 Volts, 3Ø	208Y/120 Volts, 3Ø 480Y/277 Volts, 3Ø
Amp	400 – 1200	WEMCT Series WESCT Series	WEMCT Series WESCT Series	WEMCT Series WESCT Series
Cutler-Hammer	400 – 800			CTAP Series (2) CTAT Series (2)
Erickson	400 – 1200 1200	WECT__ Series	WECT__ Series	WECT__ Series WECT__ Series
Power Distribution	400 – 800 1200 1600	WE_ 013 Series	WE_ 033 Series WE12033	WE_ 034 Series WE12034 WE16034
RJB (Galva-Closure Products)	400-800 400	WECT__ Series WE-CT__ Series (3)	WECT__ Series WE-CT__ Series (3)	WECT__ Series WE-CT__ Series (3)

(1) See table listing manufacturers' wireways for use with direct buried service laterals.

(2) For 208Y/120 volt use only. Must be used with a termination compartment or main switch.

(3) Has a fused pull-out switch or circuit breaker as the main disconnect device.

**PAD-MOUNTED CURRENT TRANSFORMER METERING (TRANSOCKETS)
WITH UNDERGROUND SERVICE LATERAL**

Service Application				Reference
1Ø	3-Wire	120/240 Volts	400-800 Amperes	
3Ø	3-Wire	240(grounded) or 480 Volts	400-4000 Amperes	
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	400-4000 Amperes	

Supplier	Ampere Rating	Transocket Catalog Numbers		
		120/240 Volts, 1Ø	240 Volts, 3Ø 480 Volts, 3Ø	208Y/120 Volts, 3Ø 480Y/277 Volts, 3Ø
AMP	1200 1600 2000 2500 3000		WESCC12-4ACTL8 WESCC16-4ACTL8 WESCC20-4ACTL8 WESCC25-4ACTL8 WESCC30-4ACTL8	WESCC12-4ACTL13 WESCC16-4ACTL13 WESCC20-4ACTL13 WESCC25-4ACTL13 WESCC30-4ACTL13
Erickson	2000 2500 3000 4000		PMCTCC4610WE PMCTCC4611WE PMCTCC4612WE PMCTCC4613WE	PMCTCC4610N-WE PMCTCC4611N-WE PMCTCC4612N-WE PMCTCC4613N-WE
RJB (Galva-Closure Products)	400 600 800 1200 1600 2000 3000	WE403-6PM WE603-6PM WE803-6PM	WE403-8PM WE603-8PM WE803-8PM WE1203-8PM WE1603-8PM WE2003-8PM	WE404-13PM WE604-13PM WE804-13PM WE1204-13PM WE1604-13PM WE2004-13PM WE3004-13PM

**WIREWAYS FOR USE
WITH UNDERGROUND SERVICE LATERALS
400 TO 1600 AMPERES, ALL VOLTAGES**

Supplier	Amp Rating	Wireway Catalog Number
AMP	800	WW (Available in 36", 48" & 60" lengths.)
Erickson	800	USR (Available in 36", 47" & 59" lengths.)
Milbank	800	MW6 (Available in 22", 36" & 48" lengths.)
RJB	800	CC (Available in 36", 48" & 60" lengths.)
AMP	1600 (1)	WWL (Available in 18" & 36" lengths.)
Erickson	1600 (1)	USRL (Available in 24", 36", 42" & 54" lengths.)
Milbank	1600 (1)	MW10 (Available in 22", 36", 48" & 60" lengths.)
RJB	1600 (1)	CCL (Available in 22", 36", 48" & 60" lengths.)

(1) For concrete encased service laterals the wireway shall extend a minimum of 3 inches to a maximum of 6 inches below final grade.

TRANSFORMER RATED METER SOCKETS

Service Application			Reference
1Ø	3-Wire	120/240 Volts	M-20 to M-26
3Ø	3-Wire	240(grounded) or 480 Volts	M-20 to M-26
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	M-20 to M-26

Supplier	Socket Catalog Numbers		
	120/240 Volts, 1Ø 6 Terminal	240 Volts, 3Ø 480 Volts, 3Ø 8 Terminal	208Y/120 Volts, 3Ø 480Y/277 Volts, 3Ø 13 Terminal
AMP	UC7532-XL	UC3887-XL	UC3889-XL
Erickson	W-130	W-330	W-340
Meter Devices	601U3128A6-301	601U3128A8-302	601U3128A13-303
Milbank	UC7532	UC3887	UC3889
RJB (Galva-Closure Products)	MS2013-6	MS2033-8	MS2034-13

**FREE STANDING CURRENT TRANSFORMER COMPARTMENTS
WITH MAIN BREAKERS OR FUSED SWITCHES**

Service Application			Reference			
1Ø	3-Wire	120/240 Volts	M-24			
3Ø	3-Wire	240 (grounded) or 480 Volts	M-24			
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	M-24			

Supplier	Ampere Rating	Catalog Numbers				
		120/240 Volts, 1Ø	240 Volts, 1Ø	480 Volts, 3Ø	208Y/120 Volts, 3Ø	480Y/277 Volts, 3Ø
AMP	400-4000	FMU Series	FMU Series	FMU Series	FMU Series	FMU Series
General Electric	400 600 800 1000 1200	SE4-WE-34-HS SE6-WE-4-HS SE8-WE-4-HS	SE4-WE-356-HS SE6-WE-56-HS SE8-WE-56-HS SE10-WE-56-HS SE12-WE-56-HS	SE4-WE-5-HS SE6-WE-5-HS SE8-WE-5-HS SE10-WE-5-HS SE12-WE-5-HS	SE4-WE-3-HS SE6-WE-HS SE8-WE-HS SE10-WE-HS SE12-WE-HS	SE4-WE-HS SE6-WE-HS SE8-WE-HS SE10-WE-HS SE12-WE-HS
Square D	400 600 800 1000 1200			CTC-364-CU CTC-366-CU CTC-368-CU CTC-3610-CU CTC-3612-CU	CTC-364-CU CTC-366-CU CTC-368-CU CTC-3610-CU CTC-3612-CU	CTC-364-CU CTC-366-CU CTC-368-CU CTC-3610-CU CTC-3612-CU

NOTE: Manufacturer to provide an approved termination compartment.

TERMINATION COMPARTMENTS

FOR USE ABOVE GRADE ONLY, WHERE THE SERVICE LATERAL ENTERS THE BOTTOM OF THE COMPARTMENT AND THE LOAD CONDUCTORS LEAVE TOP REFERENCE — PAGES U-18, U-19, U-24, U-26, & U-27					
Supplier	Ampere Rating	Catalog Numbers			
		120/240 Volt 1Ø, 3W	240 or 480 Volt 3Ø, 3W	208Y/120 Volt 3Ø, 4W	480Y/277 Volt 3Ø, 4W
AMP	400 600 800 1000 1200 1600 2000	WETC4-3AL WETC6-3AL WETC8-3AL	WETC4-8AL WETC6-8AL WETC8-8AL WETC10-8AL WETC12-8AL WETC16-8AL WETC20-8AL	WETC4-4AL WETC6-4AL WETC8-4AL WETC10-4AL WETC12-4AL WETC16-4AL WETC20-4AL	WETC4-4AL WETC6-4AL WETC8-4AL WETC10-4AL WETC12-4AL WETC16-4AL WETC20-4AL
Cutler-Hammer	400 800 1200	1UGPB400R 1UGPB800R		3UGPB400R 3UGPB800R 3UGPB1200R	3UGPB400R 3UGPB800R 3UGPB1200R
Erickson	400 800 1200 1600 2000 2500 3000 4000	WETB-365N (1) WETB-367N (1, 2)	WETB-365 (1) WETB-367 (1, 2) WETB-368 (1, 3) WETB-369 (1, 3) WETB-3610 (1, 3) WETB-3611 (1, 3) WETB-3612 (1, 3) WETB-3613 (1, 3)	WETB-465N (1) WETB-467N (1, 2) WETB-468N (1, 3) WETB-469N (1, 3) WETB-4610N (1, 3) WETB-4611N (1, 3) WETB-4612N (1, 3) WETB-4613N (1, 3)	WETB-465N (1) WETB-467N (1, 2) WETB-468N (1, 3) WETB-469N (1, 3) WETB-4610N (1, 3) WETB-4611N (1, 3) WETB-4612N (1, 3) WETB-4613N (1, 3)
General Electric	400 800 1200	TMPU4R TMPU8R		TMP3U4R TMP3U8R TMP3U12R	TMP3U4R TMP3U8R TMP3U12R
Milbank	400 600 800 800 1200 1600 2000 2500 3000	UTB413OH-WE UTB613OH-WE UTB813OH2-WE UTB813OH3-WE	UTB433OH-WE UTB633OH-WE UTB833OH2-WE UTB833OH3-WE UTB1233OH-WE UTB1633OH-WE UTB2033OH-WE UTB2533OH-WE	UTB434OH-WE UTB634OH-WE UTB834OH2-WE UTB834OH3-WE UTB1234OH-WE UTB1634OH-WE UTB2034OH-WE UTB2534OH-WE UTB3034OH-WE	UTB434OH-WE UTB634OH-WE UTB834OH2-WE UTB834OH3-WE UTB1234OH-WE UTB1634OH-WE UTB2034OH-WE UTB2534OH-WE UTB3034OH-WE
Murray	400 800 1200	DPB042W DPB082W		DPB043W DPB083W DPB123W	
RJB	400 600 800 " " 1200 1600 2000 2500 3000	TB-413-1 (1) TB-613-2 (1) TB-813-2 (1) TB-813-3 (1)	TB-433-1 (1) TB-633-2 (1) TB-833-2 (1) TB-833-3 (1) TB-1233-4 (1) TB-1633-5 (1) TB-2033-6 (1) TB-2533-7 TB-3033-8	TB-434-1 (1) TB-634-2 (1) TB-834-2 (1) TB-834-3 (1) TB-1234-4 (1) TB-1634-5 (1) TB-2034-6 (1) TB-2534-7 TB-3034-8	TB-434-1 (1) TB-634-2 (1) TB-834-2 (1) TB-834-3 (1) TB-1234-4 (1) TB-1634-5 (1) TB-2034-6 (1) TB-2534-7 TB-3034-8
Siemens	400 800 1200	WMMB1400 WMMB1800		WMMB3400 WMMB3800 WMMB31200	

- (1) Has adjustable termination pads which must be in the center or upper position when used as per Pages U-18 & U-19, U-24, U-26 & U-27.
- (2) If additional lugs are required use lug kit D-3481B.
- (3) If additional lugs are required use lug kit C-686B.

CONTINUED ON NEXT PAGE

TERMINATION COMPARTMENTS (CONTINUED)

FOR USE ABOVE GRADE ONLY, WHERE BOTH THE SERVICE LATERAL AND THE LOAD CONDUCTORS ENTER THE BOTTOM OF THE COMPARTMENT (1)					
REFERENCE — PAGES U-20, U-21, U-22, & U-23					
Supplier	Ampere Rating	Catalog Numbers			
		120/240 Volt 1Ø, 3W	240 or 480 Volt 3Ø, 3W	208Y/120 Volt 3Ø, 4W	480Y/277 Volt 3Ø, 4W
AMP	400 400 600 600 800 800 1000 1200 1600 2000	WETC4-3AL WESCC4/8-3AL WETC6-3AL WESCC4/8-3AL WETC8-3AL WESCC4/8-3AL	WETC4-8AL WESCC4/8-3AL WETC6-8AL WESCC4/8-3AL WETC8-8AL WESCC4/8-3AL WETC10-8AL WETC12-8AL WETC16-8AL WETC20-8AL	WETC4-4AL WESCC4/8-4AL WETC6-4AL WESCC4/8-4AL WETC8-4AL WESCC4/8-4AL WETC10-4AL WETC12-4AL WETC16-4AL WETC20-4AL	WETC4-4AL WESCC4/8-4AL WETC6-4AL WESCC4/8-4AL WETC8-4AL WESCC4/8-4AL WETC10-4AL WETC12-4AL WETC16-4AL WETC20-4AL
Erickson	400 800 1200 1600 2000	WETB-365N WETB-367N (2)	WETB-365 WETB-367 (2, 4) WETB-368 (3, 4) WETB-369 (3, 4) WETB-3610 (3, 4)	WETB-465N WETB-467N (2, 4) WETB-468N (3, 4) WETB-469N (3, 4) WETB-4610N (3, 4)	WETB-465N WETB-467N (2, 4) WETB-468N (3, 4) WETB-469N (3, 4) WETB-4610N (3, 4)
Milbank	800 1200 1600 2000 3000	UTB813UG-WE	UTB833UG-WE UTB1233UG-WE UTB1633UG-WE UTB2033UG-WE UTB3033UG-WE	UTB834UG-WE UTB1234UG-WE UTB1634UG-WE UTB2034UG-WE UTB3034UG-WE	UTB834UG-WE UTB1234UG-WE UTB1634UG-WE UTB2034UG-WE UTB3034UG-WE
RJB	400 600 800 1200 1600 2000 3000	TB-413-1 TB-613-2 TBWE-813-2	TB-433-1 TB-633-2 TBWE-833-2 TBWE-1233-3 TBWE-1633-4 TBWE-2033-6 TBWE-3033-8	TB-434-1 TB-634-2 TBWE-834-2 TBWE-1234-3 TBWE-1634-4 TBWE-2034-6 TBWE-3034-8	TB-434-1 TB-634-2 TBWE-834-2 TBWE-1234-3 TBWE-1634-4 TBWE-2034-6 TBWE-3034-8

- (1) Has adjustable termination pads which must be in the top position when used as per Pages U-20, U-21 or U-22, U-23.
- (2) If additional lugs are required use lug kit D-3481B.
- (3) If additional lugs are required use lug kit C-686B.
- (4) Suffix SG indicates optional side gutter for exit of load conductors.

FOR OVERHEAD SERVICE ONLY, AND WITH MANUFACTURERS BUS CONNECTED EQUIPMENT			
REFERENCE — PAGE M-23			
Supplier	Ampere Rating	Catalog Numbers	
		1Ø, 3W	3Ø, 4W
Siemens	800 1200 1600	MTB8U & WMTB8U	MTB84U & WMTB84U MTB124U & WMTB124U MTB164U & WMTB164U

CONTINUED ON NEXT PAGE

TERMINATION COMPARTMENTS (CONTINUED)

FOR USE ABOVE GRADE ONLY, AND WITH MANUFACTURERS BUS CONNECTED EQUIPMENT REFERENCE — PAGE M-23					
Supplier	Ampere Rating	Catalog Numbers			
		120/240 Volt 1Ø, 3W	240 or 480 Volt 3Ø, 3W	208Y/120 Volt 3Ø, 4W	480Y/277 Volt 3Ø, 4W
AMP	400-4000	FMU Series	FMU Series	FMU Series	FMU Series
Cutler-Hammer	400 " " 600 800 1200 1600	3MTB400R 3MTB600R 1MTB800R (1) 1MTB1600RC (2)		3MTB400R 3MTB600R 3MTB800R (1) 3MTB1600RC (2) 3MTB1600RC (2) 3MTB1600RC (2)	
Erickson	400 600 800 1200 1600 2000	WE-TRB325N WE-TRB326N WE-TRB327N	WE-TRB325 WE-TRB326 WE-TRB327 WE-TRB328 WE-TRB329 WE-TRB3210	WE-TRB425N WE-TRB426N WE-TRB427N WE-TRB428N WE-TRB429N WE-TRB4210N	WE-TRB465N WE-TRB466N WE-TRB467N WE-TRB468N WE-TRB469N WE-TRB4610N
General Electric	400 " 600	TMP3L4R TMP3L6R		TMP3L4R TMP3L6R TMP3L8R (1)	
Square D	400 600 800 1600	EZM 1400TB EZM 1800TB EZM 1800TB		EZM 3400TB EZM 3800TB EZM 3800TB EZM 31600TB	

(1) Requires lug landing kit 3MTB1200CLK.

(2) Requires lug landing kit 3MTB1600CLK.

FOR USE IN DOWNTOWN MILWAUKEE AREA WITH AC NETWORK ONLY (1) REFERENCE — PAGE U-25					
Supplier	Ampere Rating	Catalog Numbers			
		120/240 Volt 1Ø, 3W	240 or 480 Volt 3Ø, 3W	208Y/120 Volt 3Ø, 4W	480Y/277 Volt 3Ø, 4W
AMP	400 600 800 1000 1200	WETC4-3AL WETC6-3AL WETC8-3AL	WETC4-8AL WETC6-8AL WETC8-8AL WETC10-8AL WETC12-8AL	WETC4-4AL WETC6-4AL WETC8-4AL WETC10-4AL WETC12-4AL	WETC4-4AL WETC6-4AL WETC8-4AL WETC10-4AL WETC12-4AL
Erickson	400 800 1200 1600 2000 2500 3000	WETB-365N WETB-367N (2)	WETB-365 WETB-367 (2) WETB-368 (3) WETB-369 (3) WETB-3610 (3) WETB-3611 (3) WETB-3612 (3)	WETB-465N WETB-467N (2) WETB-468N (3) WETB-469N (3) WETB-4610N (3) WETB-4611N (3) WETB-4612N (3)	WETB-465N WETB-467N (2) WETB-468N (3) WETB-469N (3) WETB-4610N (3) WETB-4611N (3) WETB-4612N (3)
Hoffman	200	A18R126	A18R126	A18R126	
RJB	400 600 800 800 1200 1600 2000 3000	TB-413-1 TB-613-2 TBWE-813-2	TB-433-1 TB-633-2 TBWE-833-2 TBWE-833-3 TBWE-1233-3 TBWE-1633-4 TBWE-2033-6 TBWE-3033-8	TB-434-1 TB-634-2 TBWE-834-2 TBWE-834-3 TBWE-1234-3 TBWE-1634-4 TBWE-2034-6 TBWE-3034-8	TB-434-1 TB-634-2 TBWE-834-2 TBWE-834-3 TBWE-1234-3 TBWE-1634-4 TBWE-2034-6 TBWE-3034-8

(1) Has adjustable termination pads which must be lowered to the lowest position when used as per Page U-25.

(2) If additional lugs are required use lug kit D-3481B.

(3) If additional lugs are required use lug kit C-686B.

TERMINATION COMPARTMENT / DISCONNECT/ MAIN BREAKER/FUSE COMBINATION

	Service Application		Reference
1Ø	3-Wire	120/240 Volt	M-23
3Ø	4-Wire	208Y/120 Volt	M-23

Supplier	Ampere Rating	Catalog Number		
		120/240 Volt, 1Ø, 3W	208Y/120 Volt, 3Ø, 4W	480Y/277 Volt, 3Ø, 4W
AMP	400–4000 (2)	FMU Series	FMU Series	FMU Series
Cutler Hammer	400 (1) 600 (2) 800 (2) 1200 (2) 1600 (2) 2000 (2)	1MFS400RUG 1M(H)CB400RCL 1MFS600RUG 1M(H)CB600RCL 1MFS800RUG 1M(H)CB800RCL	3MFS400RUG 3M(H)CB400RCL 3MFS600RUG 3M(H)CB600RCL 3MFS800RUG 3M(H)CB800RCL 3MFS1200RUG 3MCB1600RUGCCL 3MCB2000RUGCCL	
Erickson	400 (1) 600 (2) 800 (2) 1200 (2) 1600 (2)	CM-BFMS325N CM-BFMS326N CM-BFMS327N	CM-BFMS425N CM-BFMS426N CM-BFMS427N CM-VLB448N-LE CM-VLB449N-LE (3) CM-VLB449N-LE-CM9 (4)	6CM-BFMS465N 6CM-BFMS466N 6CM-BFMS467N 6CM-VLB448NG6-LE 6CM-VLB449NG6-LE (3) 6CM-VLB449NG6-LE-CM9 (4)
General Electric	400 (1) 600 (2) 800 (2) 1200 (2)	TMPFB4RCLL-MOD-1 TMPFB6RCLL-MOD-1 TMPFB8RCLL-MOD-1	TMP3FB4RCLL-MOD-1 TMP3FB6RCLL TMP3FB8RCLL TMP3FB12RCLLT	
Murray	400 (1) 600 (2) 800 (2)	DT042UW DT062UW DT082UW	DT043UW DT063UW DT083UW	
Siemens	400 (1) 600 (2) 800 (2)	WMS4UPB WMS6UPB WMS8UPB	WMS44UPB WMS64UPB WMS84UPB	
Square D	400 (1) 600 (2) 800 (2) 1000 (2) 1200 (2) 1600 (2)	EZM 1400 CBU/ FSU EZM 1600 CBU/ FSU EZM 1800 CBU/ FSU	EZM 3400 CBU/ FSU EZM 3600 CBU/ FSU EZM 3800 CBU/ FSU EZM 31000 CBU EZM 31200 CBU EZM 31600 CBU	
T & B/Anchor	400 (1) 600 (2) 800 (2)	MFS4RNUG-TB MFS6RNUG-TB MFS8RNUG-TB	M3FS4RNUG-TB M3FS6RNUG-TB M3FS8RNUG-TB	

- (1) Requires set screw connectors on line side for terminating service lateral.
- (2) Requires bolts or studs for WE supplied 2-hole compression lugs on the line side for terminating service lateral.
- (3) 1200A horizontal main bus.
- (4) 1600A horizontal main bus.

PAD-MOUNTED TERMINATION COMPARTMENTS

Service Application			
1Ø	3-Wire	120/240 Volts	400-800 Amperes
3Ø	3-Wire	240(grounded) or 480 Volts	400-4000 Amperes
3Ø	4-Wire	208Y/120 or 480Y/277 Volts	400-4000 Amperes

FOR USE ABOVE GRADE ONLY, WHERE THE SERVICE LATERAL ENTERS THE BOTTOM OF THE COMPARTMENT AND THE LOAD CONDUCTORS ENTER THE BOTTOM OF THE COMPARTMENT				
Supplier	Ampere Rating	Catalog Numbers		
		120/240 Volts, 1Ø	240 or 480 Volt 3Ø, 3W	208Y/120 Volt 480Y/277 Volt 3Ø, 4W
AMP	1200 1600 2000 2500 3000		WESCC12-3AL WESCC16-3AL WESCC20-3AL WESCC25-3AL WESCC30-3AL	WESCC12-4AL WESCC16-4AL WESCC20-4AL WESCC25-4AL WESCC30-4AL
Erickson	2000 2500 3000 4000		PMCTCC3610-WETB PMCTCC3611-WETB PMCTCC3612-WETB PMCTCC3613-WETB	PMCTCC3610N-WETB PMCTCC3611N-WETB PMCTCC3612N-WETB PMCTCC3613N-WETB
RJB (Galva-Closure Products)	400 600 800 1200 1600 2000 3000	TB-413-1PM TB-613-2PM TBWE-813-2PM	TB-433-1PM TB-633-2PM TBWE-833-2PM TBWE-1233-3PM TBWE-1633-4PM TBWE-2033-6PM TBWE-3033-8PM	TB-434-1PM TB-634-2PM TBWE-834-2PM TBWE-1234-3PM TBWE-1634-4PM TBWE-2034-6PM TBWE-3034-8PM